

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification⁶ : G02F 1/1339, 1/1333</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/08151 (43) International Publication Date: 18 February 1999 (18.02.99)</p>
<p>(21) International Application Number: PCT/US97/23327 (22) International Filing Date: 17 December 1997 (17.12.97) (30) Priority Data: 08/907,744 8 August 1997 (08.08.97) US (71) Applicant: MINNESOTA MINING AND MANUFACTURING COMPANY [US/US]; 3M Center, P.O. Box 33427, Saint Paul, MN 55133-3427 (US). (72) Inventors: BRUZZONE, Charles, L.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). POKORNY, Richard, J.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). THOMAS, Patrick, A.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). AASTUEN, David, J., W.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). GARDNER, Timothy, J.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). PADIYATH, Raghunath; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). (74) Agents: MILLER, William, D. et al.; Office of Intellectual Property Counsel, P.O. Box 33427, Saint Paul, MN 55133-3427 (US).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report.</p>
<p>(54) Title: LIQUID CRYSTAL DISPLAY SUBSTRATES WITH MICRO-STRUCTURED BARRIER OVERLAYERS</p>		
<p>(57) Abstract</p> <p>Substrate elements for making liquid crystal display devices are disclosed as well as display devices using such elements. A substrate element includes a base sheet having the desired optical properties and providing the structural stability for the substrate element. The substrate element further includes a micro-structured barrier layer that protects the base sheet from adverse chemical reactions with the liquid crystal or alignment layer solvents. The micro-structured barrier layer comprises a plurality of micro-structured spacing members that provide precise, uniform spacing between the first substrate element and a second substrate element. A pair of substrate elements, at least one of which having a micro-structured barrier layer, can thereby be mated to form a display device. The substrate elements of the present invention allow large area, high resolution displays to be fabricated which will provide uniform display properties throughout the display area.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CJ	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

LIQUID CRYSTAL DISPLAY SUBSTRATES WITH MICRO-STRUCTURED BARRIER OVERLAYERS

5

Field of the Invention

The present invention relates to a substrate construction useful for making liquid crystal displays and display devices. More particularly, this invention relates to structured layers on plastic or glass based substrates where the structured layer maintains the necessary uniform spacing between device walls and provides a barrier to chemical interactions with the substrate base material.

Background of the Invention

Liquid crystal display (LCD) devices are well known and are useful in a number of applications where light weight, low power and a flat panel displays are desired. Typically, these devices comprise a pair of sheet-like, glass substrate elements, or "half-cells," overlying one another with liquid crystal material confined between the glass substrates. The substrates are sealed at their periphery with a sealant to form the cell or device. Transparent electrodes are generally applied to the interior surface of the substrates to allow the application of an electric field at various points on the substrates thereby forming addressable pixel areas on the display. Examples of useful liquid crystal materials are twisted nematic, super twisted nematic and ferroelectric liquid crystal mixtures.

It is desirable to manufacture large area displays of relatively light weight for use in portable devices such as computers, overhead projectors and the like. Certain organic, polymeric substrates are much lighter than glass and are therefore preferred for use over glass in large area, lightweight displays. However, these substrates tend to be more flexible than glass and must be separated by a dense population of spacers to maintain uniform separation between the closely spaced half cells forming the LCD device. This problem is even more severe with surface stabilized ferroelectric liquid crystal displays which require a nominal 2 μm spacing

low voltages and show uniform contrast across the entire display area. This uniform spacing is required to provide precise control of the shallow cavity containing the liquid crystal material.

Means for achieving the required spacing uniformity include using either
5 precisely dimensioned, short-length polymeric fibers or spheres as in U.S. Pat. No. 4,501,471 or spacing members made of photoresist material bonded to the substrate as in U.S. Pat. No. 4,720,173. Each of these methods has deficiencies. Fiber and spheroidal spacing particles are not easily placed uniformly on the substrate to maintain even spacing over the entire area and fibers may overlap to increase the
10 spacer height. Moreover, when the device flexes or is otherwise physically stressed, the spacers may shift or migrate to cause starved areas in the display cell. Bonded structural members must be precisely positioned on each substrate with exactly the same height, a feat that is difficult given the dimensions and tolerances required for effective liquid crystal displays. If members have different chemical composition
15 from the substrate, differential thermal expansion may occur, which causes possible fracture of the bond at the interface and shifting of the spacing member.

Many of these deficiencies were addressed by imparting polymeric substrates with a microstructure comprising uniform height ridges to maintain uniform cell gaps as disclosed in U.S. Pat. No. 5,268,782 (Wenz). The
20 microstructured substrate disclosed by Wenz provided spacers that would not shift or fracture because the microstructure was physically and chemically integral with the substrate. Therefore, no bonding was required between the spacers and the substrate with which they were integral. In addition, the fabrication of the microstructured substrate could be controlled well within a 0.1 μ m or less tolerance
25 even over large areas (tens and hundreds of square centimeters), making it possible to construct large area, light weight displays while preserving uniform contrast across the display.

One primary difficulty with the Wenz approach is that all currently available thermoplastic polymer materials suitable for the formation of the microstructured
30 ridges and having the desired optical properties tend to be soluble in or to absorb

either the liquid crystal mixtures or alignment layer solvents during processing, operation, and storage of the devices. Such reactions with the substrate polymer adversely affect the optical properties of the substrate, which may cause problems ranging from aberrations in the LCD to failure of the device.

5 To prevent interactions between the LCD material and the spacing members, the microstructured surface may be coated with a thin layer (about 500 to 2000 Angstrom) of silicon dioxide by vacuum deposition prior to contact with the liquid crystal or alignment layer materials. While the silicon dioxide layer provides an adequate barrier as deposited, formation of a complete LCD requires exposure
10 of the substrate to elevated temperatures during, for example, alignment layer processing, storage, and post-fill annealing. Exposure to these elevated temperatures causes the silicon dioxide coating to fracture, particularly at high stress points, due to the large difference in coefficients of thermal expansion between the silicon dioxide coating and the polymer substrate. The fractures in the
15 silicon dioxide layer provide areas of contact between the liquid crystal and the substrate. This may result in absorption of the liquid crystal by the substrate at these fracture points, causing local swelling of the substrate. The local swelling leads to failure of the display due to the uncontrolled optical retardation and disruption of the uniform spacing gap caused by the absorbed liquid crystal in the
20 substrate.

Polymers that are impervious to liquid crystal mixtures and to alignment layer solvents may also be applied to the spacer members to form a barrier. These polymers can be chosen or formulated to have coefficients of thermal expansion that closely match that of the substrate polymer. Polymer coatings may be applied over
25 the microstructured substrates disclosed by Wenz using methods such as coating and subsequent cross-linking of a thin liquid resin, or evaporation coating of a polymer layer, over the existing microstructure. However, such polymer coating methods are inadequate to simultaneously provide the required protection of the substrate and the required level of cell gap uniformity between the microstructured
30 ridges. Thin coatings ($< 0.1 \mu\text{m}$) do not provide an adequate barrier, whereas

thicker coatings ($> 0.1 \mu\text{m}$) do not replicate the microstructure within tolerances and thus cause display non-uniformities.

Another shortcoming with the Wenz approach is that it is not transferable to glass substrates or to substrates other than those that can be imparted with the
5 microstructure. For such substrates, less reliable spacer means, such as fibers, glass beads, and photoresist ribs would need to be employed.

A major driving force for the advancement of electronic display technology is the ability to provide larger displays having higher resolution. Such advances cannot be made without the development of substrate materials and materials
10 combinations that may be adapted to large area display applications and allow precise control of sub-micrometer dimensions.

Summary of the Invention

The present invention provides a substrate element having a microstructured
15 barrier layer between the substrate base material and the liquid crystal. The barrier layer both inhibits interactions between the liquid crystal and the substrate base material that would otherwise adversely affect the optical properties of the base material, and functions as a spacer between the substrate base and a second substrate element to ensure proper cell gaps across the LCD.

20 The present invention combines the functions of a substrate and a spacer into one substrate element. The element comprises a substantially flat substrate base material having selected optical properties and a microstructured barrier layer that provides the desired spacing. The substrate element thus developed is a two layer system, wherein the physical integrity of the system is provided by the
25 underlying base polymer while the chemical stability and microstructured spacers are provided by an unreactive layer that is adhered to the substrate base. The present invention also comprises LCD devices using such substrate elements. The present invention also comprises electronic devices using liquid crystal displays incorporating such substrate elements.

More specifically, the present invention comprises a substrate element for use as a half-cell in making electrically addressable liquid crystal displays. The substrate element comprises a base sheet either of a polymeric material or of glass having a flat profile on at least one major surface. The substrate element further
5 comprises a barrier layer having a flat profile on one major surface positioned adjacent to the flat surface of the base sheet and a microstructured profile on the opposing major surface. This microstructured profile comprises a plurality of spacing members, preferably a series of parallel ridges, each spacing member rising to a common level to support a second substrate element.

10 When incorporated in a display device, thin, transparent, conducting layers can be applied to the substrate element on the surfaces surrounding the microstructure on the barrier layer. The conducting layers allow the application of a voltage across selected portions of the uniformly spaced LCD cell gap. Other elements commonly associated with liquid crystal displays may also be associated
15 with the substrate elements to provide a half-cell for making a useful display device.

The articles of the present invention are made by known molding techniques described and exemplified hereinafter which allow microstructure features to be molded integral with the barrier layer. The dimensions of the features can be molded to very tight tolerances and are reproducible without significant variation.
20 These very precise spacing members integral with the barrier layer and precisely positioned over large areas allows the production of large area displays with uniform appearance over their entire area.

Having microstructured spacing members integral with the substrate barrier layer helps ensure a microstructured substrate element that can be made highly
25 uniform over meter-sized areas thereby providing high optical uniformity. An integral microstructure can be made to electrically isolate adjacent conductors, thus eliminating costly and yield-reducing photolithographic steps. The LCD manufacturing process is simplified because the need to separately apply spacer beads or fibers or photolithographed dots or stripes is eliminated. In addition, the
30 substrate base materials can be chosen for desired properties such as light weight

and transparency without regard for reactivity with liquid crystal mixtures or alignment layer solvents. This invention may be used with the ferroelectric liquid crystals as well as the twisted nematic, super twisted nematic, cholesteric, and other liquid crystal materials requiring accurate and precise spacing control for application
5 in high definition, large format, direct-view and projection displays.

Brief Description of the Drawings

Fig. 1 is a diagrammatic, partial, isometric view of an illustrative liquid crystal display device and associated electronics.

10 Fig. 2 is a diagrammatic, partial, isometric view of a prior art liquid crystal display device.

Fig. 3A is a schematic, cross-sectional view of the construction of the prior art liquid crystal display device having a substrate element with integral microstructure spacing elements.

15 Fig. 3B is a schematic, cross-sectional view of the construction of the liquid crystal display device of the present invention having a substrate element comprising a base sheet and a microstructured barrier layer.

Fig. 4 is a schematic representation of a preferred method of making the substrate element of the present invention.

20

Detailed Description

The term "microstructure" as used herein refers to structural elements having dimensions characteristically measured in micrometers (e.g. from about 0.1 micrometers up to 100 micrometers). The term "microstructured" as used herein
25 refers to a surface imparted with a microstructure using microreplication techniques such as those disclosed in U.S. Pat. Nos. 3,689,346, 4,244,683 and 4,576,850.

As shown in Fig. 1, a typical twisted nematic or super twisted nematic display device 10 comprises a cell formed by placing a pair of transparent, planar substrates 12 and 14, in register, overlying and spaced apart from one another. The
30 periphery of the substrates are joined and sealed with an adhesive sealant (not

shown) usually applied by a screen printing technique to provide an enclosed cell.

The shallow space or cavity between the substrates is filled with a liquid crystal material 28 just prior to final sealing. Conductive, transparent electrodes 16(a)

through 16(e) and 18(a) through 18(d) are arranged on the inside surface of the

5 substrates in either a segmented or X-Y matrix design (shown), as is well known in the art, to form a plurality of picture elements (pixels). Although only a few electrodes are shown, in practice a large number of electrodes are incorporated in the cell and the number will generally increase as the areal dimensions of the cell increase.

10 Alignment coatings 20, 22 are applied to portions of the interior surface of the liquid crystal display cell to cause a desired orientation of the liquid crystal material at its interface with the surface of the display. This ensures that the liquid crystal rotates light through angles which are complementary to the alignment of the polarizers associated with the cell. Polarizing elements 24, 26 are optional

15 depending on the type of display (polarizing elements are required for twisted nematic and super twisted nematic displays, for example), and they may be associated with one or more surfaces of the display when used. A reflector element (not shown) may be associated with the bottom substrate 12 when a reflective rather than a transmissive display is desired. In that event, bottom substrate 12 may

20 not have to be transparent.

The components and assembly techniques of liquid crystal displays as described above are well known. Details of assembly can be found in the literature such as "Liquid Crystals-Applications and Uses", Volume 1, *Bitendra Bahadur, Ed., World Scientific Publishing Co. Pte. Ltd.* (1990), Chapter 7, "Materials and

25 Assembling Process of LCDS."

Liquid crystal material fills the space between substrates 12 and 14, but for purposes of illustration, only a column of liquid crystal material 28 is shown corresponding to the area overlying common areas of the crossed electrodes 16(d) and 18(a). Arrows 30(a) through 30(e) show how the molecules of the liquid

30 crystal are aligned in a 90 degree twist in a twisted nematic cell by the alignment

layers 20, 22 in the absence of an electric field (other degrees of twist may be used for super twisted nematic cells). Arrows 30(a) and 30(e) also correspond to the direction of polarization of the polarizers 24 and 26, respectively.

Electrode leads 32(a) through 32(e) and 36(a) through 36(c) are shown
5 connected to bus leads 34 and 38, respectively, which in turn are connected to addressing electronics shown schematically at 40.

Twisted nematic liquid crystal devices employing a small amount of a chiral additive have a helical or twisted molecular orientation as shown by arrows 30(a) through 30(e) in Fig. 1. When an electric field is applied to the liquid crystal
10 material by electrodes incorporated into the device, the molecules re-orient to point in a vertical direction due to their electrical anisotropy. The molecules rotate polarized light when in the twisted state and pass light without rotation when in the untwisted vertical state. When used in combination with polarizers, this rotation of polarized light makes the display act as a light valve, either blocking or passing
15 transmitted or reflected light. The surface 42 represents a pixel area which can be turned on or off by addressing electrodes 16(d) and 18(a) simultaneously. When individually addressable electrodes are incorporated into the display, the display device may display images.

Ferroelectric liquid crystals are also useful in display devices. These
20 molecules have a polarization vector which reorients under the influence of an applied electric field. Thus, the application of an electric field ("field on condition") causes these liquid crystal molecules to orient in a characteristic way. Because they are bistable materials, they remain as oriented by the field even after the orienting electric field is removed ("field off condition"), which reduces power consumption.
25 Application of a field of different polarity can re-orient the liquid crystal materials to a different orientation characteristic of the field.

There are also many other types of liquid crystal materials which may be employed as light valves when used in conjunction with this invention. These include, but are not restricted to, cholesteric liquid crystals, polymer dispersed
30 liquid crystals, polymer stabilized cholesteric texture liquid crystals, and twisted

nematic liquid crystals used in other switching schemes such as "in plane switching."

The electrodes may be addressed independently to create an electric field at selected pixels. In some addressing schemes, the electrodes are sequentially and repeatedly scanned at a rapid rate to provide moving images similar to television images. This requires "refreshing" the display at short time intervals to rapidly turn pixels on and off. In order to switch the pixels on and off rapidly with reasonable voltage levels, the layer of liquid crystal material should be uniformly thin. The spacing between the substrates becomes critical to achieve a uniform appearance.

To prepare large area displays with uniform spacing and resulting appearance, spacers comprising microstructure elements integral with the substrate have been employed as disclosed in U.S. Pat. No. 5,268,782 (Wenz), which is incorporated herein by reference.

A portion of the liquid crystal display device disclosed by Wenz is shown in Fig. 2. The device 50 comprises a transparent bottom substrate 52 and a transparent top substrate 54. Microstructure spacing ribs 56 are integral with the substrate 52 and rise up to a common level to support the top substrate 54. Transparent conductive electrodes 58 and 60 are located on the interior of the bottom and top substrates, 52, 54, respectively, and are connected to a voltage source (not shown) for creating an electric field between opposed electrodes. Optional alignment materials 62, 64 and 66 are shown in various locations. The alignment material 64 results from the application of alignment layer 62 on bottom substrate 52 and is covered by an adhesive/sealant 68. Thus, the alignment material 64 performs no alignment function and can be eliminated if desired. The top substrate 54 is bonded to the tops of the spacing ribs 56 by the adhesive/sealant 68. The spacing ribs 56 together with the substrates 52 and 54 form a cavity in which liquid crystal material (not shown) is disposed before the cell is sealed at its periphery with an adhesive/sealant (not shown) to form a complete display device.

The substrate 52 is preferably a thermoplastic, polymeric material which can be molded using known microreplication techniques, is optically transparent and has

reasonable dimensional stability under the conditions encountered during the manufacture and use of the display device. Thermoplastic materials which are useful for the substrate 52 include, for example, polycarbonate, polyvinyl chloride, polystyrene, polymethyl methacrylate, polyurethane polyimide and polysulfuric
5 polymers, as well as other transparent thermoplastic polymers.

While suitable substrate materials provide the desired optical and structural properties, they often dissolve in or absorb either the liquid crystal mixture or the solvents used in the application of the alignment layer. Such reactions with the substrate material locally change the optical or physical properties of the substrate
10 material, creating non-uniformities in the appearance of the display or causing failure of the display through, for example, breakage of the transparent conductor induced by polymeric swelling.

Polymeric substrates that react with liquid crystal mixtures or with alignment layer solvents may be protected by providing a barrier coating. Barrier
15 coatings are thin layers of material that can be applied to the polymeric substrate at the interface between the substrate and the liquid crystal or optional alignment layer. The coating should resist diffusion of the liquid crystal and alignment layer solvent and thereby inhibit adverse reactions with the substrate material. The coating should also perform its barrier function without being so thick or uneven as
20 to affect the uniformity of the cell gap across the display. One possible barrier coating comprises a silicon dioxide thin film that may be applied by known vacuum deposition techniques. For example, silicon dioxide films with thicknesses in the range of about 500 to about 2000 Angstrom may be applied over the microstructured substrate element disclosed by the '782 patent to Wenz. The
25 silicon dioxide barrier film is impervious to the liquid crystal mixture or alignment layer solvents and may be evenly coated so that the uniformity of the cell gap across the display is not affected by the coating.

However, inorganic thin film barrier layers, such as silicon dioxide coatings, that can be deposited evenly have largely different coefficients of thermal expansion
30 as compared to the polymeric materials that may be used to make the substrate.

Typical inorganic films will have coefficients of thermal expansion of about 1×10^{-6} to 5×10^{-6} per °C, while typical polymers have coefficients of thermal expansion greater than 1×10^{-5} per °C. Coefficients of thermal expansion for thermoplastics become increasingly large as the temperature approaches the glass transition temperature of the thermoplastic. Many processing temperatures approach the glass transition temperature for thermoplastics. For example, alignment layer curing is done above 150 °C and preferably above 180 °C. Also, after filling the device with the liquid crystal mixture, there often is a post-fill annealing step performed at about 90 °C to 120 °C. During elevated temperature processing, storage, and operation steps, (performed at about 100 - 150 °C for plastic cells), the polymer substrate and the inorganic barrier layer expand (during heating) and contract (during cooling) by different amounts, leading to cracking and fracturing of the barrier layer, especially at high stress points such as at the extremities of the microstructured spacing ridges or at discontinuities in the transparent conductor layer. Once fracturing has occurred, the inorganic coating can no longer work as a barrier.

Polymeric materials can also be employed as barrier coatings. A polymeric material may be formulated to have a coefficient of thermal expansion that matches or nearly matches that of the substrate material so that cracks and fractures are not formed in the barrier layer upon elevated temperature processing, storage, or operation. However, to obtain a high quality polymer film (uniform thickness, without pinholes, and without defects caused by small particulates), film thicknesses should be on the order of about 0.2 μm to more than 10 μm . Thus, polymer barrier layers may be employed successfully on substantially flat substrates because even coatings that do not affect the uniformity of the cell gap across the display can easily be obtained using commonly known techniques. When coating a microstructured substrate, however, the application of sufficiently thick films (those thicker than 0.1 μm) disrupts the cell gap uniformity, especially in devices requiring small cell gaps.

The construction of the substrate elements of the present invention is shown schematically in cross-section in Fig. 3B and is compared to the construction of the substrate elements disclosed by the '782 patent to Wenz as shown schematically in cross-section in Fig. 3A. It should be noted that the relative dimensions of the individual features of these constructions are not drawn to scale.

The Wenz construction 100 of Fig. 3A includes a microstructured bottom substrate 104 and a flat profile top substrate 102 set off from the bottom substrate 104 by microstructured ridges 114 that are physically and chemically integral with the bottom substrate. Each substrate has deposited thereon transparent conductive layers 106. On the microstructured substrate 104, the ridges 114 act to physically isolate the conductive layers so that there is no electrical shortage between the independently addressable cells. Optional alignment layer coatings 108 may also be applied over the substrate and conductive layers. The top substrate 102 is bonded to the ridges of the bottom substrate 104 by a thin layer of an adhesive 110 applied to the tops of the ridges. Each region 112 defined by the cell gap between the top and bottom substrate and separated by individual ridges is then filled with liquid crystal and the periphery of the construction is sealed to complete the liquid crystal display device. The construction 100 is in all ways analogous to the device 50 shown in Fig. 2.

The construction of the present invention is shown in Fig. 3B. The construction 120 comprises a top substrate base 122A and a bottom substrate base 122B having substantially flat profiles. The top substrate base 122A has applied thereto a thin barrier layer 124 that also has a substantially flat profile. The bottom substrate base 122B has applied thereto a thin barrier layer 126 having a microstructured profile comprising spacing members 136 that rise to a common height above the base of the barrier layer to create a uniform gap 134 across the device between the bottom and top substrates. Each barrier layer 124, 126 has applied thereto at least one thin, transparent, conductive layer 128 to provide independently addressable regions that define the individual cells of the display. An optional alignment layer 130 may be provided over the barrier layers 124, 126 and

transparent conductive layer 128. The top substrate element 122A may be bonded to the bottom substrate element 122B by applying a thin layer of an adhesive material 132 to the tops of the microstructured spacing members 136 that are integral with the barrier layer 126 of the bottom substrate 122B.

5 The present invention thus employs a two-layer substrate element comprising a base substrate sheet 122B having a flat profile, and a microstructured barrier layer 126 that protects the base sheet from the liquid crystal and the alignment layer solvents. The barrier layer 126 also provides uniform height spacing members that ensure uniform cell gaps.

10 The substrate base 122 can be any material that has the desired optical properties, can be formed into a sheet with a thickness in the range 50 to 1500 μm having a substantially flat profile, and is stable up to the highest processing temperatures used to form a completed display (typically less than about 200 $^{\circ}\text{C}$). The substrate base material is preferably a glass or a thermoplastic, polymeric
15 material which is optically transparent and has reasonable dimensional stability under the conditions encountered during the manufacture and use of the display device. Thermoplastic materials which are useful in this regard include, for example, polycarbonate, polyvinyl chloride, polystyrene, polymethyl methacrylate, polyurethane, polyimide, polyacrylates, amorphous polyolefins, and polysulfuric
20 polymers as well as other transparent thermoplastic polymers. Because the substrate base material is not imparted with the microstructured spacing members, it is not necessary that the substrate base material be moldable using known microreplication techniques, in contrast with the substrate element disclosed by the '782 patent to Wenz.

25 The barrier layer 126 can be any material that acts as a barrier to diffusion of liquid crystal mixtures and/or alignment layer solvents and that can be molded with microstructured spacing members by methods described hereinafter. The barrier layer material should also adhere to the substrate base material, either by itself or with the aid of an adhesive at the interface, without delaminating under conditions
30 of processing, storage, or operation. In addition, the transparent conducting layer

128 should be able to adhere to the barrier layer 126. Other desirable barrier layer material properties include transparency, stability at elevated temperatures (up to about 200 °C, depending on the processing conditions), scratch resistance, low or no birefringence, and low or no ionic contamination. It should be noted, however, that the optical requirements on the barrier layer are less severe than those on the substrate base because the barrier layer can be much thinner than the substrate base. A thinner barrier layer will tend to reduce any adverse optical effects that a thicker barrier layer may cause.

To provide barrier layers free of pinholes or other defects (such as those due to small particulates, i.e. less than 0.5 μm), the thickness of the barrier layer in the areas between the microstructured spacing members is preferably about or greater than 1 μm . This thickness is called the "land" thickness. The land thickness of the barrier layer is more preferably about or greater than 5 μm . However, the land should not be so thick that the barrier layer causes substantial discoloration in the display or otherwise adversely affects the optical properties of the substrate element. An appropriate land thickness will depend on the particular formulation of the barrier layer material.

The resistance of a barrier layer material to liquid crystal mixtures may be tested by measuring the diffusion of toluene through a 0.5 μm thick film of the material. Toluene may be used as a substitute for typical liquid crystal mixtures because it elicits similar responses from the polymer due to its chemical similarity to liquid crystal materials, but it does so more rapidly and at lower expense. The barrier layer material is considered impervious to the toluene if no diffusion through the film is detected after an exposure time of about 30 minutes. A similar test may be employed to measure the resistance of the candidate material to various alignment layer solvents.

The barrier layer material is preferably an acrylate and more preferably an acrylate curable by exposure to ultraviolet radiation during a molding process as is described hereinafter. The particular barrier layer material is best chosen or formulated based on the choice of substrate base material. Once the base material is

chosen, an acrylate may be readily formulated to have adequate adherence to the base material and to have a coefficient of thermal expansion that closely matches that of the base material. When formulating the barrier layer material, close attention should also be paid to the properties identified above.

5 The barrier layer material may also enhance the structural stability of the substrate element. Because polymer-based substrate elements tend to be less rigid than glass-based substrate elements, polymer-based substrate elements often have a tendency to deform under local stresses. Although small deformations often do not affect the optical function of the display, they may cause cracking or breakage in the transparent conducting layers. A crack in a transparent conducting layer may cause an entire row of pixels to fail. By choosing a barrier layer material such as a cross-linked acrylate, the barrier layer may provide extra dimensional stability to the substrate element so that deformation of the substrate element under local stresses is less likely. Thus, the two layer construction of the present invention allows the formation of wholly polymer-based substrate elements that are less susceptible to deformation.

 The microstructured spacing members may be any plurality of protrusions that rise to a common level and can support a second, opposing substrate element. Preferably, the microstructured spacing members comprise a series of parallel ridges that rise to a common level. Other types of protrusions that can perform the function of the spacing members may also be employed. For example, an array of post-like protrusions of various cross-sectional geometries can serve as spacing members. The microstructured spacing members can be provided by the microreplication and molding methods described hereinafter.

25 The lateral distance between the spacing members is measured, for example, from center to center of adjacent spacing members 136 in Fig. 3B. This dimension can vary considerably depending on the particular application for the display device. For example, the lateral distance between spacing members may range from about 5 μm up to 1000 μm . The width of the spacing members can range from about 1 or 2 μm up to several micrometers, e.g. about 25 μm or more. The upper limit is

30

governed by the inactive area that can be tolerated in a given display, while the lower limit will depend on the required strength against delamination of a pair of bonded substrate elements (narrower spacing members produce less bonding area for opposing substrate elements). Typically, it is desired to have at least 50% active area in a display. That is, the projected surface area of the spacing members should occupy no more than about one-half of the total substrate surface in the display area. For a substrate where the spacing members are of substantially equal surface dimensions, the lateral spacing between spacing members would be at least about 1 times the width of the spacing member in the direction being measured and could be 10 times the width or more. In addition, it is generally desired to have at least about 10 pixels per cm (25 lines per inch) in a horizontal or vertical direction, up to about 120 or 240 pixels per cm (300 to 600 lines per inch) for high resolution displays, and up to about 400 pixels per cm (1000 lines per inch) for very high resolution displays.

The cell gap of the device is controlled by the height of the microstructured spacing members. The height of the spacing members above the land can range from about 1 or 2 μm up to several micrometers or tens of micrometers depending on the type of liquid crystal used. For example, surface stabilized ferroelectric liquid crystal displays typically require a nominal 2 μm cell gap.

Electrode materials useful in the present invention include commonly known transparent conducting oxides, such as indium-tin-oxide (ITO) and other materials commonly used in LCD's. Typically the conductive materials are vapor deposited onto the surface of the substrate, and in the case of the present invention directly onto the barrier layer, by sputtering or other commonly known techniques. Because vapor deposition techniques are not able to be directed with sufficient accuracy, conductive material may be deposited on the tops of the spacing members. If left in place, this conductive region could possibly short across the electrode regions on the opposing substrate element. Various techniques can be used to remove conductive material from the tops of the spacing members such as, for example, burnishing the tops of the spacing members after deposition, etching the conductive

layer off while protecting the desired electrode surface with photoresist, etc. When the etching technique is used, a positive photoresist is applied to the entire substrate element surface. The photoresist on the tops of the spacing members must then be removed to expose the transparent conductor. This can be accomplished if the

5 photoresist on the tops of the spacing members is, for example, selectively exposed to light either by the use of a mask, a laser selectively targeted on the spacing member tops, or by the use of a prism atop the spacing members so that light is transmitted to the photoresist at the prism/photoresist interface, but is reflected at the prism/air interface. After selective exposure, the photoresist on the tops of the

10 spacing members may be removed. The exposed portions of the substrate are then subjected to an etchant to remove the conductive layer from the tops of the spacing members. After removal of the exposed conductive layers, the remaining photoresist may be stripped away and the alignment coating and/or other materials may be applied as desired.

15 The alignment compositions useful in the present invention are also well known in the art. These are various polymeric material applied from solvents by spin coating or other techniques commonly used which will supply a thin, uniform coating across the surface of the substrate element. Once applied, these materials may be dried and rubbed with cloth or other materials to provide an orienting

20 surface which will align liquid crystal molecules in contact with the surface. A preferred alignment material is a nylon polymer which can be solvent coated and rubbed with cloth, such as velvet, to provide a useful alignment layer. The most commonly used alignment layer material is polyimide. Other liquid crystal

25 alignment techniques include photoalignment using polarized light or ultraviolet radiation, the use of oriented silicon dioxide films as alignment layers, and other techniques known to skilled artisans.

The microstructured barrier layer of the present invention can be made by a microreplication technique utilizing embossing or injection molding. This process is described in U.S. Pat. Nos. 3,689,346, 4,244,683 and 4,576,850. The process

30 involves the preparation of a microstructured mold master using conventional

techniques. The mold master is then filled with a polymerizable composition which is exposed to radiation to rapidly polymerize the composition. The polymerized composition is then removed from the mold master to provide a polymerized article which has a microstructured surface replicated from the mold master.

5 In the barrier layer of the present invention, the land thickness is often too thin to provide structural support that would allow the barrier layer to stand alone. Thus, it is preferred to impart the barrier layer with the microstructure while the barrier layer resin is in contact with the substrate base sheet. In this way, the substrate base provides the physical stability for the substrate element. In addition,
10 the barrier material can be cross linked with the substrate base during polymerization so that when the microreplication master is removed, the molded barrier layer is adhered to the substrate base sheet. One method of so forming a substrate element involves thermal coextrusion of the barrier layer with the base film wherein the barrier layer is subsequently imparted with the microstructure and
15 then cooled.

A more preferred method for making the substrate element of the present invention is shown schematically in Fig. 4. This process involves coating a liquid resin 152 that is curable using ultraviolet (UV) radiation onto a sheet of a substrate base material 150. Preferred materials for the resin 152 include UV curable epoxy
20 acrylates. The means for applying the UV curable resin is shown schematically as 154. The substrate base sheet 150 coated with the barrier layer resin 152 is advanced toward a drum 156 and a nip roll 158 combination. The drum surface 157 is fitted with microreplication master plates that comprise a microstructure pattern that is the inverse of the pattern to be imparted into the barrier layer coating.
25 Pressure is applied between the nip roll 158 and the drum surface 157. The ultimate land thickness of the barrier coating can be controlled by adjusting the pressure between the nip roll and the drum. Contact with the drum 156 is maintained by a second nip roll 162, and while still in contact with the drum surface, the liquid resin is exposed to UV radiation from a UV source 160. The barrier coating is thereby
30 cured to form a film 164 comprising a microstructured barrier layer adhered to a

base sheet, which may be cut with the appropriate dimensions to produce a substrate element suitable for inclusion in a liquid crystal display device.

Using the method shown in Fig. 4 to impart the barrier layer with microstructured spacing members comprising substantially parallel ridges, square
5 substrate elements were made having display areas of about 4 cm² to about 16 cm². The spacing ridges had a nominal height in the range 1.7 to 5.6 μm, the width of the ridges was in the range 20 to 60 μm, and the spacing between the ridges was in the range 200 to 300 μm. In all of these ranges barrier layers were molded having uniform ridge heights to within 25 nm (0.025 μm), yielding uniform cell gaps to
10 within 50 nm (0.05 μm) over the entire display area when bonded to another substrate element.

In order to provide optical uniformity over the microstructure-spaced liquid crystal display, it is necessary to ensure that the spacing members remain in contact with the mating substrate of the LCD cell so that the design spacing is maintained.
15 One solution is to adhesively bond each spacing member to the mating substrate. This is not a simple matter since the spacing members may be only a few micrometers high while adhesives are usually coated to several micrometers in thickness. Conventional coating methods such as knife coating, gravure coating, etc., would produce too thick a coating and would also put adhesive in the channels
20 between spacing members which would prevent filling with liquid crystal.

One method of applying adhesive to the ribs has been disclosed by the '782 patent to Wenz and is referred to as the "tack-off," or selective transfer, method. In this method an adhesive is thinned in a solvent, applied uniformly to a flat substrate (carrier), dried to a few tenths of a micrometer thickness, and then "tacked off"
25 onto the tops of the microstructured spacing members by rolling the structured side of the microstructured surface across the thin adhesive layer. The thin adhesive never touches the channel portions of the microstructure and thus is not transferred into the channels. Once adhesive has been applied to the spacing members, the mating substrate can then be bonded to the microstructured substrate element to

form a pair of half-cells that may be filled with liquid crystal and sealed at their periphery to form a completed liquid crystal display.

Although particular embodiments of the invention have been described and illustrated herein, skilled artisans will recognize that changes in form and detail may
5 be made without departing from the spirit or the scope of the invention.

WHAT IS CLAIMED IS:

1. A substrate element for a liquid crystal display comprising:
 - a base sheet having a substantially flat profile on at least one
 - 5 major surface thereof;
 - a barrier layer comprising:
 - a first major surface having a substantially flat profile,
 - wherein the first major surface is adjacent to the substantially
 - flat surface of the base sheet, and
 - 10 a second major surface having a plurality of
 - microstructured spacing members, wherein each spacing
 - member rises to substantially the same height; and
 - independently addressable, electrically conductive areas
 - positioned adjacent to the barrier layer.
- 15 2. The substrate element of claim 1, wherein the plurality of spacing members comprises a plurality of protruding, substantially parallel ridges.
3. The substrate element of claim 1, wherein the plurality of spacing
- 20 members comprises a plurality of post-like protrusions.
4. The substrate element of claim 1, wherein the base sheet is a thermoplastic.
- 25 5. The substrate element of claim 1, wherein the base sheet is a transparent thermoplastic.
6. The substrate element of claim 1, wherein the base sheet is glass.

7. The substrate element of claim 1, wherein the base sheet is made of a material with a glass transition temperature greater than about 150 degrees centigrade.
- 5 8. The substrate element of claim 1, wherein the barrier layer is selected from the group consisting of epoxy acrylates.
9. The substrate element of claim 1, wherein the barrier layer is selected from the group consisting of epoxy acrylates curable by exposure to
10 ultraviolet radiation.
10. The substrate element of claim 1, wherein the spacing members rise to an average height of from about 1 to about 25 micrometers above the second major surface of the barrier layer.
- 15 11. The substrate element of claim 1, wherein the thickness of the barrier layer everywhere exceeds approximately 0.2 micrometers.
12. The substrate element of claim 1, wherein the thickness of the barrier
20 layer everywhere exceeds approximately 0.5 micrometers.
13. The substrate element of claim 1, wherein the electrically conductive areas are positioned on the microstructured surface of the barrier layer.
- 25 14. The substrate element of claim 1, wherein the electrically conductive areas are positioned between the barrier layer and the base sheet.
15. A liquid crystal display comprising:
a first half-cell and a second half-cell forming a pair of half-cells in
30 overlying register with one another and confining a liquid

crystal material therebetween, each half-cell including independently addressable, electrically conductive areas, wherein the first half-cells comprises:

a base sheet having a substantially flat profile on at least one

5

major surface thereof; and

a barrier layer comprising:

a first major surface having a substantially flat profile,

wherein the first major surface is adjacent to the substantially flat surface of the base sheet, and

10

a second major surface having a plurality of

microstructured spacing members, the plurality of spacing members comprising a plurality of protruding, substantially parallel ridges each rising to substantially the same level, wherein the ridges support the second, overlying half-cell at a substantially uniform distance from the first half-cell.

15

20

16. The display of claim 15, wherein the second half-cell has a substantially flat major surface, and wherein the substantially flat major surface of the second half-cell is adhesively bonded to at least a portion of the microstructured spacing members of the first half-cell.

25

17. An electronic device comprising:

a liquid crystal display comprising a first half-cell and a second half-cell forming a pair of half-cells in overlying register with one another and confining a liquid crystal material therebetween, each half-cell including independently addressable,

electrically conductive areas, wherein the first half-cells comprises:

a base sheet having a substantially flat profile on at least one major surface thereof; and

5 a barrier layer comprising:

a first major surface having a substantially flat profile, wherein the first major surface is adjacent to the substantially flat surface of the base sheet, and

10 a second major surface having a plurality of microstructured spacing members, the plurality of spacing members comprising a plurality of protruding, substantially parallel ridges each rising to substantially the same level, wherein the ridges support the second, overlying half-cell at a substantially uniform distance from the first half-cell.

20 18. A method of making a substrate element for an electrically addressable liquid crystal display comprising the steps of:

providing a base sheet having a substantially flat profile on at least one major surface thereof;

forming a barrier layer having a first major surface and a

25 second major surface, wherein the first major surface is substantially flat and the second major surface has imparted thereto a microstructured profile comprising a plurality of spacing members each rising to substantially the same level;

adhering the substantially flat first major surface of the barrier layer to the substantially flat major surface of the base sheet; and

forming independently addressable, electrically conductive areas adjacent to the barrier layer.

5

19. The method of claim 18, wherein the steps of forming the barrier layer and adhering the barrier layer to the base sheet are performed by coating the substantially flat major surface of the base sheet with a liquid resin layer, imparting the resin layer with the microstructured profile, and curing the resin to simultaneously form the barrier layer and adhere the barrier layer to the base sheet.

10

20. The method of claim 19, wherein the resin is an epoxy acrylate curable by exposure to ultraviolet radiation.

15




Fig. 1




Fig. 2
PRIOR ART




Fig. 3A
PRIOR ART




Fig. 3B




Fig. 4

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 97/23327

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G02F1/1339 G02F1/1333

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G02F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 196 02 632 A (SAMSUNG DISPLAY DEVICES CO LTD) 1 August 1996 see the whole document	1,3,6, 10-12, 14,15,17
A	US 4 744 639 A (TSUBOYAMA AKIRA) 17 May 1988 see column 2 see column 4, line 57 - column 6, line 50; figures 3,5; example 1	1-3,6, 8-12, 15-17
A	US 5 268 782 A (WENZ ROBERT P ET AL) 7 December 1993 cited in the application see the whole document	1-6, 13-18

-/--

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"Z" document member of the same patent family

Date of the actual completion of the international search

20 April 1998

Date of mailing of the international search report

27/04/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Stang, I

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 97/23327

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>EP 0 747 749 A (KANEKAFUCHI CHEMICAL IND)</p> <p>11 December 1996</p> <p>see page 3, line 1 - line 25</p> <p>see page 5, line 5 - line 23</p> <p>-----</p>	4,5,7-12

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/23327

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 19602632 A	01-08-1996	JP 8248428 A US 5668617 A	27-09-1996 16-09-1997
US 4744639 A	17-05-1988	JP 61147232 A	04-07-1986
US 5268782 A	07-12-1993	CA 2085631 A CN 1075016 A,B DE 69312099 D DE 69312099 T EP 0552104 A JP 5264982 A MX 9300134 A US 5545280 A	17-07-1993 04-08-1993 21-08-1997 12-02-1998 21-07-1993 15-10-1993 01-07-1993 13-08-1996
EP 0747749 A	11-12-1996	CN 1141086 A WO 9523353 A	22-01-1997 31-08-1995